

Ethanol CDA 19 200 Proof

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade name	Ethanol CDA 19 200 Proof		
Synonyms	Denatured Alcohol		
Use	Industrial use, Raw material for chemical processes, Raw material for industry, Solvent		
Company	Sasol Chemicals (USA) LLC (an affiliate of Sasol Chemicals North America LLC)		
Address	12120 Wickchester Lane Houston TX 77079		
Telephone	CHEMTREC North America Transportation Emergency (24-hr)		(800) 424-9300
	CHEMTREC World Wide		(703) 527-3887
	Other Emergencies (24-hr)		(337) 494-5142
	MSDS and Product Information (8:00am-4:30pm CST)		(281) 588-3491
	Health and Safety Information (7:30am-4:00pm CST)		(281) 588-3492
E-mail address	SasolElectronicSDS@us.sasol.com		

SECTION 2 HAZARDS IDENTIFICATION

GHS Hazards

Flammable liquids	Category 2
Eye irritation	Category 2A
Acute toxicity (Inhalation)	Category 4
Carcinogenicity	Category 2

LABEL ELEMENTS**Hazard symbols****Signal word** Danger

Hazard statements	H225 Highly flammable liquid and vapour.
	H319 Causes serious eye irritation.
	H332 Harmful if inhaled.
	H351 Suspected of causing cancer.

Precautionary statements

Prevention	P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
	P233 Keep container tightly closed.
	P240 Ground/bond container and receiving equipment.
	P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Ethanol CDA 19 200 Proof

- P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P280 Wear protective gloves/ eye protection/ face protection.
 P264 Wash skin thoroughly after handling.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P271 Use only outdoors or in a well-ventilated area.
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.

- Response** P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P312 Call a POISON CENTER or doctor/ physician if you feel unwell.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.

- Storage** P403 + P405 + P235 Store locked up in a well-ventilated place. Keep cool.

- Disposal** P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS-No.</u>	<u>Weight percent</u>
Ethanol	64-17-5	95
Methyl isobutyl ketone	108-10-1	4
Heptane	142-82-5	1

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.

SECTION 4 FIRST AID MEASURES

- Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
- Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.
- Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of shortness of breath, give oxygen. Call a physician immediately.

Ethanol CDA 19 200 Proof

Ingestion If swallowed, call a poison control centre or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

SECTION 5 FIREFIGHTING MEASURES

FLAMMABLE PROPERTIES

Fire/explosion Flash back possible over considerable distance. NFPA Class IB flammable liquid.

Suitable extinguishing media Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO₂)

Protective equipment and precautions for firefighters Wear self-contained breathing apparatus and protective suit. Keep containers and surroundings cool with water spray.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up Evacuate personnel to safe areas. Remove all sources of ignition. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Do not flush into surface water or sanitary sewer system.

Spill precautions Material can create slippery conditions.

SECTION 7 HANDLING AND STORAGE

Safe handling advice Ensure all equipment is electrically grounded before beginning transfer operations. Keep away from heat and sources of ignition.

Storage/Transport pressure Ambient

Load/Unload temperature Ambient

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES

Ensure adequate ventilation, especially in confined areas.

PERSONAL PROTECTIVE EQUIPMENT

Eyes Wear as appropriate: Goggles, Face-shield

Skin Wear suitable protective clothing, gloves and eye/face protection.

Ethanol CDA 19 200 Proof

Inhalation Respiratory protection is normally not required except in emergencies or when conditions cause excessive airborne levels of mists or vapors. Use NIOSH approved respiratory protection.

EXPOSURE GUIDELINES

<u>Components</u>	<u>Exposure limit(s)</u>
Ethanol	ACGIH STEL 1,000 ppm OSHA PEL 1,000 ppm 1,900 mg/m ³
Methyl isobutyl ketone	OSHA PEL 100 ppm 410 mg/m ³ ACGIH TLV (8-hour) 20 ppm ACGIH STEL 75 ppm
Heptane	OSHA PEL 500 ppm 2,000 mg/m ³ ACGIH TLV (8-hour) 400 ppm 1,640 mg/m ³ ACGIH STEL 500 ppm 2,050 mg/m ³ NIOSH Ceiling 440 ppm 1,800 mg/m ³

PEL= Permissible Exposure Limits

TLV= Threshold Limit Value

EL= Excursion Limit

TWA= Time Weighted Average (8 hr.)

STEL= Short Term Exposure Limit (15 min.)

WEEL= Workplace Environmental Exposure Level

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid;

Colour Clear, colorless

Form liquid

Odour alcohol-like

Odour Threshold no data available

Flash point 13 °C, 55 °F;

Flammability Upper explosion limit: 20.0 %(V)

Lower explosion limit: 4.0 %(V)

Boiling point/boiling range 74 - 80 °C, 165.2 - 176 °F;

Melting point/range ca. -114 °C, -173 °F;

Auto-ignition temperature ca. 400 °C, 752 °F;

Decomposition temperature no data available

Ethanol CDA 19 200 Proof

Flammability (solid, gas)	no data available
Vapour pressure	ca. 66.661 hPa @ 20 °C, 68 °F;
Vapour density	ca. 1.5
Density	0.79 g/cm ³ @ 15.5 °C, 60 °F;
Specific gravity	no data available
Water solubility	completely miscible
Viscosity	no data available
pH	no data available
Evaporation rate	no data available
Partition coefficient: n-octanol/water	no data available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	Stable at normal ambient temperature and pressure.
Chemical stability	No decomposition if stored and applied as directed.
Conditions to avoid	Keep away from heat and sources of ignition.
Hazardous decomposition products	Combustion products include carbon dioxide, carbon monoxide and possibly other unidentified organic compounds.
Materials to avoid	Can react with strong oxidizers, inorganic acids, and halogens.
Hazardous polymerisation	None.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute dermal toxicity	LD50 Rabbit: > 2,000 mg/kg; OECD Test Guideline 402 Test substance: Ethanol; (literature value) LD50 Rabbit: > 2,000 mg/kg Test substance: MIBK; (literature value) LD50: > 2,000 mg/kg Test substance: Heptane
Acute inhalation	LC50 Mouse (4 hours): > 20 mg/l

Ethanol CDA 19 200 Proof

toxicity	Test substance: Ethanol; (literature value) LC50 Rat (4 hours): > 10 - 20 mg/l Test substance: MIBK; (literature value) LC50 Rat (4 hours): > 29.29 mg/l Test substance: Heptane
Acute oral toxicity	LD50 Rat: 2,000 mg/kg; OECD Test Guideline 401 Test substance: Ethanol; (literature value) LD50 Rat: > 2,000 mg/kg Test substance: MIBK; (literature value) LD50 Rat: > 5,000 mg/kg Test substance: Heptane
Skin corrosion/irritation	(Rabbit): OECD Test Guideline 404 Test substance: Ethanol Not irritating, (literature value) (Rabbit) Test substance: MIBK slight irritation, (literature value) (Rabbit): 4 hours Test substance: Heptane irritating
Eye damage/irritation	(Rabbit): OECD Test Guideline 405 Test substance: Ethanol irritating, (literature value) (Rabbit) Test substance: MIBK irritating, (literature value) Test substance: Heptane Not irritating
Respiratory or skin sensitization	Guinea pig: not sensitizing; Maximisation Test (GPMT) Ethanol, (literature value) Guinea pig: not sensitizing; Maximisation Test (GPMT) MIBK, (literature value)
Germ cell mutagenicity	Genotoxicity in vitro: Type: Ames test; OECD Test Guideline 471 System: Salmonella typhimurium; with and without metabolic activation Result: In vitro tests did not show mutagenic effects Test substance: Ethanol (literature value) Type: Ames test

Ethanol CDA 19 200 Proof

System: Salmonella typhimurium; with and without metabolic activation

Result: In vitro tests did not show mutagenic effects

Test substance: MIBK
(literature value)

Result: In vitro tests did not show mutagenic effects

Test substance: Heptane

Genotoxicity in vivo:

no data available

Assessment Mutagenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity**Reproductive toxicity:**

male and female Rat; Inhalation; OECD Test Guideline 416

NOAEL (parents): 3,000 mg/kg

NOAEL (F1): 3,000 mg/kg

NOAEL (F2): 3,000 mg/kg

Test substance: Heptane

no data available

Assessment Reproductive toxicity:

Based on available data, the classification criteria are not met.

Teratogenicity:

Mouse; OECD Test Guideline 414

NOAEL (teratogen): 3,000 mg/kg

NOAEL (maternal): 900 mg/kg

Test substance: Heptane

Rat; OECD Test Guideline 414

NOAEL (teratogen): 9,000 mg/kg

NOAEL (maternal): 3,000 mg/kg

Test substance: Heptane

Assessment teratogenicity:

Based on available data, the classification criteria are not met.

STOT - single exposure no data available

STOT - repeated exposure Rat; Oral; 90-day;
NOAEL: 1,730 mg/kg
LOAEL: 3,160 mg/kg
Test substance: Ethanol
Based on available data, the classification criteria are not met.

Aspiration toxicity no data available

Carcinogenicity **Assessment carcinogenicity:**
Suspected of causing cancer.

Carcinogenicity ratings

Methyl isobutyl ketone

Ethanol CDA 19 200 Proof

IARC Group 2B: Possibly carcinogenic to humans

SECTION 12 ECOLOGICAL INFORMATION

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)) 96 hours: > 100 mg/l; flow-through test
 Test substance: Ethanol
 (literature value)

LC50 (Danio rerio (zebra fish)) 96 hours: > 100 mg/l; static test
 Test substance: MIBK
 (literature value)

Toxicity to aquatic invertebrates EC50 (Ceriodaphnia dubia (water flea)) 48 hours: > 100 mg/l; static test
 Test substance: Ethanol
 (literature value)

EC50 (Daphnia magna (Water flea)) 48 hours: > 100 mg/l; static test
 Test substance: MIBK
 (literature value)

Toxicity to algae EC50 (Chlorella vulgaris) 72 hours: > 100 mg/l; static test; OECD Test Guideline 201
 Test substance: Ethanol
 (literature value)

Chronic toxicity to aquatic invertebrates NOEC (Ceriodaphnia dubia (water flea)) 10 d: 9.6 mg/l; semi-static test
 Test substance: Ethanol
 (literature value)

NOEC (Daphnia magna (Water flea)) 21 d: > 10 - 100 mg/l; semi-static test; OECD Test Guideline 211
 Test substance: MIBK
 (literature value)

Biodegradation Readily biodegradable

OECD Test Guideline 301B (28 d): > 60 %
 Test substance: Ethanol
 (literature value)

OECD Test Guideline 301F (28 d): > 60 %
 Test substance: MIBK
 (literature value)

Bioaccumulation Test substance: Ethanol
 No bioaccumulation is to be expected (log Pow <= 4).

Test substance: MIBK
 No bioaccumulation is to be expected (log Pow <= 4).

Mobility in soil no data available

Other adverse effects no data available

Ethanol CDA 19 200 Proof

SECTION 13 DISPOSAL CONSIDERATIONS

- Waste Code** D001 - Ignitability (RQ 100 LB). This product has the RCRA characteristic of ignitability. Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification.
- Disposal methods** Dispose of only in accordance with local, state, and federal regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.
- Empty containers.** Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

SECTION 14 TRANSPORT INFORMATION

- DOT** UN 1170, Ethanol solutions, 3, II
(RQ MIBK) When shipped in quantities greater than 125,000 lbs, RQ must be added to the shipping description.
- IATA** UN 1170, Ethanol solutions, 3, II
(RQ MIBK) When shipped in quantities greater than 125,000 lbs, RQ must be added to the shipping description.
- IMDG** UN 1170, Ethanol solutions, 3, II
(RQ MIBK) When shipped in quantities greater than 125,000 lbs, RQ must be added to the shipping description.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks no data available

SECTION 15 REGULATORY INFORMATION**U.S. FEDERAL REGULATIONS****OSHA Hazards (HCS 1994)**

Flammable liquid, Eye irritation, Skin irritation

TSCA Inventory Listing**Components**

Ethanol

2-Pentanone, 4-methyl-

Heptane

CAS-No.

64-17-5

108-10-1

142-82-5

Ethanol CDA 19 200 Proof

SARA 302 Status

Components

CAS-No.

Weight percent

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Classification

"Fire hazard", "Immediate (acute) health hazard", "Delayed (chronic) health hazard"

SARA 313 Chemical

Components

CAS-No.

Weight percent

2-Pentanone, 4-methyl-

108-10-1

4 %

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components

Reportable Quantity

Weight percent

2-Pentanone, 4-methyl-

5,000 LB

4 %

INTERNATIONAL REGULATIONS

WHMIS Classification

Class B, Division 2: Flammable liquid.

Class D, Division 2, Subdivision A: Very toxic material

Class D, Division 2, Subdivision B: Toxic material.

European Union

Classification according to Regulation (EU) 1272/2008.

Flammable liquids, Category 2

Eye irritation, Category 2

Acute toxicity (Inhalation), Category 4

Carcinogenicity, Category 2

Australia. Inventory of Chemical Substances (AICS)

Listed

Japan. Inventory of Existing and New Chemical Substances (ENCS)

Listed

Japan. Industrial Safety & Health Law (ISHL) Inventory

Listed

Canada. Domestic Substances List (DSL) Inventory

Listed

Canadian Non-Domestic Substance Listing (NDSL)

Not listed

European Inventory of Existing Commercial Chemical Substances (EINECS) Listing

Listed

Philippines. Inventory of Chemicals / Chemical Substances (PICCS)

Listed

Korea. Existing Chemicals Inventory (KECI)

Listed

China. Inventory of Existing Chemical Substances (IECSC)

Listed

Mexico. National Inventory of Chemical Substances (INSQ)

Listed

New Zealand. Inventory of Chemicals (NZIoC)

Listed

Ethanol CDA 19 200 Proof

Switzerland. Inventory of Notified New Substances (CHINV)	Listed
Taiwan. National Existing Chemical Inventory (NECI)	Listed

Please note: The names and CAS numbers which are used for this product in the stated inventories may deviate from the information which is listed in Section 3.

STATE REGULATIONS

California Prop. 65

Components

2-Pentanone, 4-methyl-

CAS-No.

108-10-1

SECTION 16 OTHER INFORMATION

HAZARD RATINGS

	<u>Health</u>	<u>Flammability</u>	<u>Physical Hazard/ Instability</u>
HMIS®	2	3	0
NFPA	2	3	0

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR SASOL CHEMICALS (USA) LLC'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH SASOL CHEMICALS (USA) LLC CONSIDERS ACCURATE AND RELIABLE, SASOL CHEMICALS (USA) LLC MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.
