

GALENOL® 2800 Emulsifier

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade name	GALENOL® 2800 Emulsifier		
Synonyms	Ethoxylated Alcohol, Cetareth-30, Alkyl Polyglycol Ether		
Use	Surfactant, Emulsifier, Raw material for cosmetic agents		
Company	Sasol Chemicals (USA) LLC (an affiliate of Sasol Chemicals North America LLC)		
Address	12120 Wickchester Lane Houston TX 77079		
Telephone	CHEMTREC North America Transportation Emergency (24-hr)		(800) 424-9300
	CHEMTREC World Wide		(703) 527-3887
	Other Emergencies (24-hr)		(337) 494-5142
	MSDS and Product Information (8:00am-4:30pm CST)		(281) 588-3491
	Health and Safety Information (7:30am-4:00pm CST)		(281) 588-3492
E-mail address	SasolElectronicSDS@us.sasol.com		

SECTION 2 HAZARDS IDENTIFICATION

GHS Hazards

Acute toxicity (Oral)	Category 4
Eye irritation	Category 2B

LABEL ELEMENTS

Hazard symbols



Signal word Warning

Hazard statements H302 Harmful if swallowed.
H320 Causes eye irritation.

Precautionary statements

Prevention P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Response P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.
P330 Rinse mouth.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

GALENOL® 2800 Emulsifier

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Disposal P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS-No.</u>	<u>Weight percent</u>
Alcohols, C16-C18, ethoxylated	68439-49-6	100

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.

SECTION 4 FIRST AID MEASURES

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.

Inhalation Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

Ingestion If swallowed, call a poison control centre or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

SECTION 5 FIREFIGHTING MEASURES

FLAMMABLE PROPERTIES

Fire/explosion NFPA Class IIIB combustible liquid.

Suitable extinguishing media Water spray, Foam, Dry chemical, Carbon dioxide (CO₂)

Protective equipment and precautions for firefighters Wear self contained breathing apparatus for fire fighting if necessary.

Further information Keep containers and surroundings cool with water spray. Do not use a solid water stream as it may scatter and spread fire. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6 ACCIDENTAL RELEASE MEASURES

GALENOL® 2800 Emulsifier

Methods and materials for containment and cleaning up Evacuate personnel to safe areas. Remove all sources of ignition. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Spilled material will solidify. Sweep up and shovel into suitable containers for disposal. Do not flush into surface water or sanitary sewer system.

SECTION 7 HANDLING AND STORAGE

Safe handling advice Take precautionary measures against static discharges.

Storage/Transport pressure Ambient

Load/Unload temperature 54 - 66 °C (For liquid product)
130 - 150 °F

Storage and handling materials Suitable: Carbon steel coated with baked phenolic. Any moisture may cause rusting of carbon steel. If product is moisture free, uncoated carbon steel tanks.

Further information on storage conditions When stored in the liquid form, ethoxylates should be padded with a dry inert gas, such as nitrogen, to prevent oxygen or air from entering the tank. Prolonged storage in the presence of air or oxygen may cause product degradation. Oxidation is not expected when stored under a nitrogen atmosphere. Inert gas blanket and breathing system needed to maintain color stability. Use dry inert gas having at least -40°C (-40°F) dew point.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES

Ensure adequate ventilation, especially in confined areas. Trace amounts of ethylene oxide may be present in the product and could accumulate in vapor spaces of storage or transport vessels.

PERSONAL PROTECTIVE EQUIPMENT

Eyes Wear as appropriate: Goggles, Face-shield

Skin Full protective clothing, chemical boots, and chemical gloves. High standards of skin care and personal hygiene should be exercised at all times.

Inhalation Use respirator when performing operations involving potential exposure to vapour of the product. Use NIOSH approved respiratory protection.

EXPOSURE GUIDELINES

There are no exposure limits established for this product. Trace amounts of ethylene oxide may be present in this product., The ethylene oxide in this product is not expected to result in significant exposures or present a health hazard.

GALENOL® 2800 Emulsifier**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	solid;
Colour	white
Form	Pastilles, solid
Odour	slight
Odour Threshold	no data available
Flash point	estimated > 175 °C, > 347 °F;
Flammability	Upper explosion limit: no data available Lower explosion limit: no data available
Boiling point/boiling range	250 °C, 482 °F;
Melting point/range	45 - 49 °C, 113 - 120 °F;
Auto-ignition temperature	Not available
Decomposition temperature	no data available
Flammability (solid, gas)	no data available
Vapour pressure	0.001 mm Hg @ 20 °C, 68 °F;
Vapour density	> 1
Density	1.023 g/cm ³ @ 60 °C, 140 °F;
Specific gravity	no data available
Water solubility	soluble
Viscosity	no data available
Viscosity, dynamic	45 mPa.s @ 70 °C, 158 °F;
pH	5 - 7
Evaporation rate	no data available
Partition coefficient: n-octanol/water	no data available

GALENOL® 2800 Emulsifier

SECTION 10 STABILITY AND REACTIVITY

Reactivity	Stable at normal ambient temperature and pressure.
Chemical stability	No decomposition if stored and applied as directed.
Conditions to avoid	Reacts slowly with air or oxygen. Storage under heated conditions in the presence of air or oxygen increases reaction rate. For example, after storing at 95°F/35°C for 30 days in the presence of air, there is measureable oxidation of the ethoxylate. Lower temperatures will allow for longer storage time and higher temperatures will shorten the storage time if stored under an air or oxygen atmosphere.
Hazardous decomposition products	When storing this product in air or oxygen, decomposition may occur, generating vapors which could be irritating. Ensure adequate ventilation, especially in confined areas. Oxidation is not expected when stored under a nitrogen atmosphere.
Materials to avoid	Can react with strong oxidizers, inorganic acids, and halogens.
Hazardous polymerisation	None.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute dermal toxicity	no data available
Acute inhalation toxicity	LC50 value expected to exceed the saturated vapor concentration in air.
Acute oral toxicity	LD50: > 1,000 mg/kg
Skin corrosion/irritation	Primary irritation (rabbit): 4 hours; 0.1 (Max. score is 8.0.) Not irritating
Eye damage/irritation	slight irritation
Respiratory or skin sensitization	no data available
Germ cell mutagenicity	Genotoxicity in vitro: no data available Genotoxicity in vivo: no data available Assessment Mutagenicity: no data available
Reproductive toxicity	Reproductive toxicity: no data available Assessment Reproductive toxicity: no data available

GALENOL® 2800 Emulsifier

Teratogenicity:
no data available

Assessment teratogenicity:
no data available

STOT - single exposure no data available

STOT - repeated exposure no data available

Aspiration toxicity no data available

Carcinogenicity **Assessment carcinogenicity:**
No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

SECTION 12 ECOLOGICAL INFORMATION

Toxicity to fish LC50 (Danio rerio (zebra fish)) 96 hours: > 1 - 10 mg/l
Test substance: C1618-25 Ethoxylate

Toxicity to aquatic invertebrates EC50 (Daphnia magna (Water flea)) 48 hours: > 100 mg/l
Test substance: C1618-25 Ethoxylate

Toxicity to algae ErC50 (Desmodesmus subspicatus (green algae)) 72 hours: > 100 mg/l
Test substance: C1618-25 Ethoxylate

Chronic toxicity to fish no data available

Chronic toxicity to aquatic invertebrates no data available

Biodegradation Readily biodegradable.

OECD Test Guideline 301B (28 d): > 60 %
Test substance: C1618-25 Ethoxylate

Bioaccumulation no data available

Mobility in soil no data available

Other adverse effects no data available

SECTION 13 DISPOSAL CONSIDERATIONS

GALENOL® 2800 Emulsifier

Waste Code Any unused product or empty containers may be disposed of as non-hazardous in accordance with state and federal requirements. Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification. If the resulting material is determined to be hazardous, please dispose in accordance with state and federal (40 CFR 262) hazardous waste regulations.

Disposal methods Dispose of only in accordance with local, state, and federal regulations.

Empty containers. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

SECTION 14 TRANSPORT INFORMATION

DOT Not regulated.

IATA Not regulated.

IMDG Not regulated.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks no data available

SECTION 15 REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

OSHA Hazards (HCS 1994)
Non-hazardous substance

TSCA Inventory Listing

Components

Alcohols, C16-C18, ethoxylated

CAS-No.

68439-49-6

SARA 302 Status

Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

CAS-No.

Weight percent

SARA 311/312 Classification

"Immediate (acute) health hazard"

SARA 313 Chemical

Components

CAS-No.

Weight percent

GALENOL® 2800 Emulsifier

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components

none

Reportable Quantity

Weight percent

INTERNATIONAL REGULATIONS

WHMIS Classification

Class D, Division 2, Subdivision B: Toxic material.

European Union

Classification according to Regulation (EU) 1272/2008.

Acute toxicity (Oral), Category 4

Eye irritation, Category 2

Australia. Inventory of Chemical Substances (AICS)	Listed
Japan. Inventory of Existing and New Chemical Substances (ENCS)	Listed
Japan. Industrial Safety & Health Law (ISHL) Inventory	Listed
Canada. Domestic Substances List (DSL) Inventory	Listed
Canadian Non-Domestic Substance Listing (NDSL)	Not listed
European Inventory of Existing Commercial Chemical Substances (EINECS) Listing	Listed
Philippines. Inventory of Chemicals / Chemical Substances (PICCS)	Listed
Korea. Existing Chemicals Inventory (KECI)	Listed
China. Inventory of Existing Chemical Substances (IECSC)	Listed
Mexico. National Inventory of Chemical Substances (INSQ)	Not listed
New Zealand. Inventory of Chemicals (NZIoC)	Listed
Switzerland. Inventory of Notified New Substances (CHINV)	Listed
Taiwan. National Existing Chemical Inventory (NECI)	Listed

Please note: The names and CAS numbers which are used for this product in the stated inventories may deviate from the information which is listed in Section 3.

GALENOL® 2800 Emulsifier

STATE REGULATIONS**California Prop. 65****Components**

Ethylene Oxide

CAS-No.

75-21-8

Sasol Chemicals (USA) LLC's ethoxylates may contain detectable quantities of ethylene oxide which is a chemical on the California Proposition 65 list. The level is typically below 1.0 ppm, although it may vary. The manufacturing process is controlled to reduce the residual ethylene oxide content.

SECTION 16 OTHER INFORMATION

HAZARD RATINGS

	<u>Health</u>	<u>Flammability</u>	<u>Physical Hazard/ Instability</u>
HMIS®	1	1	0
NFPA	1	1	0

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR SASOL CHEMICALS (USA) LLC'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH SASOL CHEMICALS (USA) LLC CONSIDERS ACCURATE AND RELIABLE, SASOL CHEMICALS (USA) LLC MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.
