

Ethanol SDA 23A 200

Product Specification - Version 6a

Formulation	Amount	Lbs	Wt%
Ethanol 200pf	100.00 usg	660.97 lbs	92.58
Acetone	8.00 usg	52.96 lbs	7.42
		713.93 lbs	100.00
Resultant Volume @ 60F per 27CFR	107.90 usg		

Specifications	Target	Minimum	Maximum	Test Method
Density @ 60F (lbs/gal)	6.616	6.611	6.626	ASTM D4052
Specific Gravity @ 60/60F	0.7942	0.7938	0.7956	ASTM D891
Suspended Matter (visual)		Free of suspended matter		ASTM D3741
Color (Pt-Co)			5	ASTM D5386/D1209
Odor		Characteristic		ASTM E769
Acidity as Acetic Acid (wt%)			0.005	ASTM D1613
Non-Volatile Matter (g/100ml)			0.005	ASTM D1353
Water Content (wt%)			0.1	ASTM D1364
Gas Chromatography Analysis (wt% Anhydrous Basis)				
Ethanol	92.58	91.84	93.32	ASTM E1100
Acetone	7.42	6.68	8.16	ASTM E1100

Notes: None

Reason for revision:

Version 2a dated 7/1/06 GAT– New format.

Version 4a dated 12/25/06 GAT – Specification layout revised for posting on website.

Version 5a dated 11/5/13 GAT – Color D5386/D1209

Version 6a dated 7/31/14 GAT – Sasol Chemicals (USA) LLC

Sasol Chemicals (USA) LLC

900 Threadneedle, Suite 100
Houston, TX 77079
Telephone: (+1) 281 588 3000
www.sasol.com