

LPA® 170 Solvent

Technical Data Sheet



sasol
reaching new frontiers



Description

LPA® 170 is a high-purity mixture of hydrotreated isoparaffins and naphthenics with very low levels of polynuclear aromatics. It is an excellent process solvent with high flash point and narrow boiling range.

Applications

LPA® 170 Solvent may be used in a wide array of applications. Applications vary widely and include metal lubricants, specialty coatings, pesticide formulations, consumer products, chemical process solvents, oilfied drilling fluids, degreasers, lamp oil, metal rolling oils, freeze point depressants, etc.

Regulatory Compliance

If this material is used in a consumer product or in certain other specific applications, some exemptions may apply. Please contact a sales representative for more information on particular FDA regulations or for solvent status as an LVP-VOC for consumer products.

Contact Information

For technical information:

Sasol North America

Product Steward

2201 Old Spanish Trail

Westlake, Louisiana 70669

Telephone: (337)494-4133

Fax: (281)368-0819

TDS.ProductSteward@us.sasol.com

For sales and pricing information contact a sales representative at:

Sasol North America

900 Threadneedle

Houston, TX 77079-2990

Telephone: (281)588-3000

Fax: (281)368-1531

info@us.sasol.com

Physical Properties

Typical physical properties are listed in the table below. Actual properties may vary from lot to lot.

Typical Properties	Method	LPA® 170 Solvent
Distillation Range, °F		
IBP		390
10%	ASTM D-86	428
90%		434
95%		438
EP		480
Flash Point, (Tag CC) °F	ASTM D-56	>170
Pour Point, °F	ASTM D-97	<-94
Specific Gravity 60°F/60°F	ASTM D-287	0.805 – 0.825
Density, lbs/gal @ 60°F	ASTM D-287	6.72 – 6.88
Average Molecular Weight	API	172
Aromatics - BTEX, ppm	EPA 8260B	ND*
Color, Saybolt Universal	ASTM D-156	>25
Relative Evaporative Rate (n-Butyl Acetate = 1)	ASTM D-3539	0.02
Vapor Pressure, torr @ 20°C	API, calc	0.05
Viscosity, cSt @ 20°C	ASTM D-445	2.4
@ 40°C		1.7
Aniline Point, °F	ASTM D-611	164
Kauri-Butanol Value	ASTM D-1133	31
Solubility parameters, (MPa) ^{1/2}	Calculated	15.9
Bromine Number	ASTM D-1159	<0.2
Nitrogen, ppm		<1
Sulfur, ppm		<1
Water, ppm	Karl-Fischer	<50

* - detection limit 36 ppb

The preceding data is based on tests and experience, which Sasol North America believes reliable, and is supplied for informational purposes only. Sasol North America expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained therein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Sasol North America with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Sasol North America.

For detailed safety and handling information regarding these products please refer to the respective Sasol North America Material Safety Data Sheet

07/22/13